



ARC 500

Stud Welding Unit
for ARC stud welding
according to current standards

Technical Data	
Welding range	Dia. 14 ga to 5/16", #4 to 7/16" (dia. 2 to 8 mm, M3 to M10 (Type RD))
Welding material	Mild steel, stainless steel
Welding rate	5 to 15 studs/min (depending on application and stud dia.)
Welding current	580 A
Welding time	5 to 350 msec
Primary power	230/460 V, 3 phases, 50/60 Hz, 50/35 AT or 575 V, 3 phases, 50/60 Hz, 25 AT (alternative input voltages available)
Power source	Transformer/Rectifier
Cooling type	F (temperature controlled cooling fan)
IP-Code	IP 23
Dimension L x W x H	18.50" x 9.06" x 8.66" (470 x 230 x 220 mm) without handle
Weight	68.34 lbs (31 kg)
Order No.	230/460 V: 93-16-0401A 575V: 93-15-0401A
General Information	
Application	
<ul style="list-style-type: none"> Especially suitable for thicker sheets of about 2 mm or higher ISO – especially suitable for attaching cut-to-length ARC-ISO and Fiberfix pins; also material with high heat resistance; excellent for insulation applications in building construction and fire-resistant insulation (FRI) 	
Process variants	
<ul style="list-style-type: none"> Short cycle drawn arc welding Drawn arc welding 	
Equipment	
<ul style="list-style-type: none"> Welding with ceramic ferrule (series) 	



Advantages

Features

- **Microcontroller** – for precise process times, optimal functional reliability and maximum operating convenience
- **Function monitoring** – automatic function test following power-up; monitoring of all internal system functions
- **Display of error codes** – on digital display
- **Lift test** – for gap welding guns

Structure

- **Extremely easy to operate**
- **Compact**
- **Robust** – metal housing withstands rough treatment in shop and on site

Safety

- With integrated **mains filter** (protection against voltage peaks)
- **Optimal for construction sites with large mains voltage fluctuations** – use even with critical voltage supply (- 10 % + 10 %)
- **EMC test**
- **High-voltage test with log**
- **Retriggering lock-out** – prevents welding on a welding element that has already been set
- **Thermal monitoring of transformer** – automatic shutdown in case of overheating
- **Temperature-regulated ventilator** – reduces noise and dust in the stud welding unit (greater system reliability)
- **Consistent separation of transformer and control unit** – protects electronic components against dust and thermal loading
- **Control unit galvanically separated from welding lines** – high degree of functional safety
- **Cooling-air tunnel** – channelling of cooling air to the transformer protects electronic components against dirt and dust
- **Optimal protection against external interferences**
- **IP-Code: IP 23**
- Also permits operation outdoors

Welding

- **Display** – infinitely adjustable power setting; easy monitoring of all functions via LED displays; display of welding time; control and monitoring of all system functions
- **Powerful** – built-in power reserves
- **Trouble-free changing** of welding voltage polarity possible by reconnecting welding current and ground cables

Suitable stud welding guns

- **A 12, A 16, AI 06**
- **CA 08**

Issue 11/13
(Technical data may change)