



# Production Fastening Systems, L.L.C.

New Orleans, LA

## SLP Pneumatic Tube Supports



Prod Id	Turning Radius	Alloy	Max No Of Tubing 1/4	Max No Of Tubing 3/8	Weight per 100 pcs
<b>SLP-2</b>	1 7/8"	SS-316 or Zinc	2	1	9 lbs
<b>SLP-3</b>	2"	SS-316 or Zinc	4	3	13 lbs
<b>SLP-4</b>	2 1/2"	SS-316 or Zinc	8	5	16 lbs
<b>SLP-6</b>	3 3/4"	SS-316 or Zinc	12	8	22 lbs
<b>SLP-8</b>	5"	SS-316 or Zinc	12+	12	28 lbs

In shipbuilding, offshore platform, and steel fabrication projects, maintaining pneumatic tubing is essential to the work at hand. At PFS, we offer easy-to-install, corrosion-resistant stud mount pneumatic tube supports to ensure that your tubing systems are protected at all times.

Our SLP tapped tube supports fasten to 3/8-16 studs and can support pneumatic tubing sized 1/4 in. through 3/4 in. PFS's SLP-type stud mount pneumatic tube supports are manufactured from grade 316 stainless steel, and are used with standard line clamps, resulting in a durable, convenient tube support method.

PFS's stud mount pneumatic tube supports are:

- Quick and simple to install (supports fasten easily onto welded studs)
- Made of corrosion-resistant grade 316 stainless steel (other alloys also available)
- Adjustable (to allow increase or decrease in number of tubing runs)
- Mounted to 3/8 in. diameter studs (to allow for standardization of electrical and pneumatic weld stud supports)
- Designed to prevent rust from accumulating (the studs allow for the tubing to stand off the base material to prevent corrosion)

\*When ordering pneumatic tube supports from PFS, please specify metric by placing an "M" after part number of cable hanger request (Example: P15002-ESL2 M).

WWW.PFSNO.COM  
SALES@PFSNO.COM



Ph: 800-216-1827  
504-427-1562  
Fax: 504-891-6229